



Breathe deep and let go of things

# medineb 300<sup>†</sup>Ultrasonic Nebulizer

### Application

For prevention, alleviation and therapy of respiratory tract disorders

The ultrasonic-nebulizer *medineb 300*+converts electrical energy with a frequency of 1.72MHz into mechanical oscillation.

These high frequency oscillations cause the smallest aerosol particles to detach from the inhalation liquid.

The resultant aerosol particle size is below 5 microns which is small enough to deliver the aerosol into the respiratory tract, bronchi and alveoli.

The *medineb 300*<sup>+</sup>is designed for the delivery of all commonly inhaled medications in the treatment of various respiratory diseases and includes the delivery of hypertonic saline for bronchial provocation testing and for sputum

Smallest quantities (3-30 ml) of medicaments are nebulized except for a small residue. Additional equipment like mouthpiece and mask support the specific treatment.

Due to easy handling and noiseless operation the medineb 300+is also especially suitable for intensive care.

High operating security because of automatic frequency-swing and electronic prevention from operation without liquid makes this product easy to handle. Air stream and intensity are infinitely variable.

The self-regulating continuous feeding system makes the use of stock bottles of up to 2 liters possible.

The application of sterile-water systems is easily possible without change. All parts that need to be cleaned can be detached comfortably by means of a plug-in connection.

# The medineb 300

Thanks to its high-quality quartz, *medineb* 300<sup>†</sup>is particularly suitable for long-time nebulization, e.g. with bedridden patients breathing through the mouth during the night (uninterrupted

Removable quartz
All our systems are completely equipped available, ready for immediate application. The quartz can be simply removed from the ultrasonic cup with the aid of an assembly device, e.g. in order to also autoclave the ultrasonic cup.

Water-refill warning signal
To protect the quartz from overheating and to ensure better therapeutic safety, a visual signal (red light-emitting diode) will indicate an insufficient water-supply.

medineb 300<sup>+</sup>meets highest hygiene requirements due to the use of disposable articles like the dust filter and the bacteria filter for the

All parts getting into contact with the patient and the aerosol are suitable for sterilization or disinfection respectively.

Autoclavable ultrasonic cup (without quartz) for still more hygienic safety, e.g. for MRSA-patients.

# Hygienic safety for the patient is the prime

Conventional ultrasonic nebulizers are frequently contaminated and the risk of infection is always

A closed sterile water system constitutes a sure and safe solution of the problem.

The risk of infection through watergerms is reduced decisively



### **Heated inhalation**

Any ultrasonic-nebulizer type micro is available with connection for heating.

The heating cable consists of an adapter with casted heating cable and connection cable with plug and is simply placed into the regular aerosol-tube.

# Table-mount

medineb 300<sup>+</sup>Ultrasonic Nebulizer in tablemounted version is particularly suitable for use at home or in doctor's practices. For fast moisturization of the respiratory tract to alleviate acute discomfort (e.g. in case of pseudocroup - laryngitis) at home and primarily in the doctor's practice, therapy with medineb 300<sup>+</sup> is a very effective natural method of treatment.

## System included:

Incl. medicament-cup and bonnet for nebulizing smallest quantities from 3 ml on. Additional water-control-device complete with cannula for diverse bottle systems for continuous nebulizing. Fitted with support for aerosol tube, air-regulation-valve, autoclavable chamber, bacteria filter, mains cable



M.E.D. Licence No.: 664/40920

**Technical data** Voltage: Frequency: 50/60 Hz 90 VA Power: Protection class: HF-frequency: 1.72 MHZ 10 % 100 % Deviation: Cont. operation: Classification: ΙB Weight: 4,5 kg Standby Power: <1 VĂ 12 months

Output 220~230 V AC Nebulizing temp.: Air quantity:

max.,30 l/min (Adjustable) 0.4 - 5 µm max. 200 mg/l Particle size: Mist density: Nebulizing output:  $0.5 - 3.9 \, \text{ml/min}$ (Adjustable) Timer Operaton: Ùp to 150min

37° °C

Manufactured in accordance with EU-guidelines 93/42/EEC